

6B Series Tractor

Open Station



JOHN DEERE



6B Series Tractor

Open Station



JOHN DEERE

ENGINE	6095B	6110B	6120B	6135B
Rated power (97/68EC) hp (kW)	95hp (70kW)	110hp (81kW)	120hp (88kW)	135hp (99kW)
Constant Power Range, rpm	1950 -2200	1600 - 2200		
Torque Reserve, percentage (%)	22	29	29	29
Maximum Torque, Nm (at 1600 engine rpm)	375Nm	452Nm	494Nm	555Nm
Rated Speed, rpm	2200rpm			
Engine Manufacturer	John Deere Power Systems			
Engine Type (4 Cylinder), Displacement	4.5L PowerTech M	4.5L PowerTech E		
Fuel System	Mechanical Rotary	High Pressure Common Rail		
Cooling system	Water Cooled Serial Radiator, Fixed Fan System			
TRANSMISSION				
Type	12F/4R DC TSS 30K 24F/12R WC TSS 30K HLP 24F/12R WC TSS 40K HLP			
Clutch	Dry Clutch	Dry Clutch / Wet Clutch		
REAR AXLE and FINAL DRIVES				
Permissible tread Setting - Front axle, mm	1625 - 2025	1740 - 2036		
Permissible tread Setting - Rear axle, mm	1613-2013		1620-2020	
Engagement - Front differential lock	N / A			
Engagement - Rear differential lock	Mechanical			
Front Axle type	Mechanical Front Wheel Drive			
Rear Axle type	Flanged Rear Axle			
Turning Radius, meter (measured without front fenders)	4.30 meter	5.50 meter		
STEERING				
Type	Hydrostatic			
HYDRAULIC SYSTEM				
Type	Open center / Constant Flow			
Flow at rated engine speed L/min	50 L/min	60 L/min		
Selective Control Valves (number and position)	2/3 Hydraulic Selective Control Valves, Rear			
3- POINT HITCH REAR				
Type	Heavy Duty, mechanical draft and position control			
Category	Category II, ball-end type hitch arms			
Lift Capacity (measured at 610mm behind hook point)	2500kg	3300kg		
REAR POWER TAKE-OFF (PTO), 540/1000 rpm				
Type	Mechanical	Mechanical	Electro-hydraulically Operated PTO	
Clutch Type	Dry Clutch	Dry Clutch / Wet Clutch		
PTO Speed Change	Mechanical Reversible - Stub Shaft			
PTO Shaft	6 Spline / 540rpm or 21 Spline / 1000rpm Stub Shaft			
Engine rpm at rated PTO speed	2200rpm			
OPEN OPERATOR STATION				
Type	Two Post Roll Over Protective structure (ROPS) with Canopy (w/o lights in canopy)			
Instrument Panel	Integrated dashboard display			
CAPACITIES				
Fuel Tank (L)	150L	220L		
DIMENSIONS and WEIGHTS				
Wheelbase (mm)	2310mm	2560mm		
Ground clearance (mm), Center MFWD without front ball	395mm	425mm	455mm	455mm
Tractor weight (kg) (shipping weight no ballasting)	4200kg	4290kg	4520kg	4520kg
Maximum permissible Gross Weight (kg)	6150kg	6800kg	8000kg	8000kg
WHEELS and TIRES				
Front Wheels	12.4-24	13.6-24	14.9-24	14.9-24
Rear Wheels	16.9-34	18.4-34	18.4-38	18.4-38

For more information, please contact our authorized dealer or nearest area office.

This literature has been compiled for broad circulation in sub-Saharan Africa. While general information, pictures and descriptions are provided, some illustrations and text may include finance product options and accessories not available in all regions. Please contact your local dealer for details. John Deere reserves the right to change specification and design of products described in this literature without notice. The green and yellow colour scheme, the leaping deer logo and the JOHN DEERE word mark are trademarks of Deere & Company.



PT WAHANA INTI SELARAS
 Operational Office : Green Sedayu Bizpark, Blok GS 3/38,
 Jl. Cakung Cilincing Timur Raya KM 2, Jakarta 13910, INDONESIA
 Phone : (+6221) 2983 2045, 2983 2113
 Email : admin.sales@wiselgroup.indomobil.co.id
 Website : www.johndeere.indomobil.com

Authorized Dealer for John Deere/Case IH Limited
Tractor - Farm Equipment