

# CH570 Cane Harvester





# CH570 Cane Harvester



## Engine

Model	John Deere 6090T PowerTech (Tier II)
Cylinders / Displacement	6 in line / 9.0 L
Power	251 Kw (337 Hp)
Air intake	Turbo and after-cooler [air-to-air]
Injection pump electronically controlled	
Optional engines:	
251 Kw (337 Hp) engine Tier III, or IV	
280 Kw (375 Hp) engine Tier II, III, or IV	

## Transmission

Two hydrostatic pumps providing variable speed	
Wheel machine:	0 to 24.6 km/h (15.3 mph)*
Track machine:	0 to 9.0 km/h (5.6 mph)*
*(Top speed dependent on tire and/or hydraulic system option)	

## Tank Capacities

Fuel	605 L (160 Gal)
Hydraulic oil	405 L (106 Gal)
Diesel Exhaust Fluid (DEF) (Tier 4)	54 L (14 Gal)

## Tires

Front:	Firestone 14x17.5 – 10 Ply w/IF
Rear:	Galaxy 23.5x25 – 20 Ply Industrial w/Ag Lug
Option:	
Front:	Firestone 14-17.5 (14-Ply) with:
Rear:	Michelin 23.5 x 25 Industrial

## Tracks

Sealed track chains	
457.2 mm (18 in) track shoes	
Options:	
Sealed and lubricated track chains	
41 cm (16 in), 51 cm (20 in), track pad widths	
Bent track shoes	

## Topper

Standard whole topper with gathering drums	
Maximum reach 5.2 m (17ft)	
Options:	
Shredder topper	
Extensions for standard topper	
Extended width whole topper	

## Crop Dividers & Knockdown Rollers

Manual adjustable tilt	
Options:	
Hydraulic tilt	
Side knives	
Floating crop dividers	
Crop dividers vines cutter knives	

## Basecutter

61 cm (24 in) circular basecutter discs	
Bolt-on wear plates for basecutter legs	
Options:	
56 cm (22 in) basecutter disc	
Contour basecutter height control	
Breakaway basecutter legs	

## Butt lifter

Three paddle closed type	
Options:	
3 paddle open butt lifter	
4 bar open butt lifter	

## Feed Rollers

Five fixed rollers below cane mat	
Five floating rollers above cane mat	

## Chopper

Eight blade differential chopper system	
95 mm blades	
Options:	
Six blade chopper	
Eight or ten blade overlap chopper	

## Primary Extractor

Polyethylene plastic 152 cm (5 ft) hood	
Four blade fan	
Options: Duraliner steel wear ring	

## Elevator

Loading to either left or right side	
Perforated floor	
Adjustable loading flap	
Options: Elevator extensions	

## Secondary Extractor

Polyethylene plastic 90 cm (3 ft) hood	
Three blade fan	
Options: Less secondary extractor	

## Comfort and Security

Pressurized cab with air conditioning and heating systems	
Front tipping cab	
Air suspension operator seat with swivel	
Training seat	
Adjustable side mirrors	
Speedometer	
Windshield wiper with water nozzle	
Side glass wipers	
Water and chemical fire extinguishers	
Anti-slip platforms in service areas	
Reverse alarm	
Engine compartment working light	
Signal and warning lights	
12 operating lights (including headlights)	
Battery remote jump start terminals	
AM/FM Radio with auxiliary input	
Refrigerator	
Compliant with all applicable standards	

## Other Optional Features

Auxiliary LED lights
Beacon lights
Service tool kits

For more information, please contact our authorized dealer or nearest area office.



### PT WAHANA INTI SELARAS

Operational Office : Green Sedayu Bizpark, Blok GS 3/38,  
Jl. Cakung Cilincing Timur Raya KM 2, Jakarta 13910, INDONESIA  
Phone : (+6221) 2983 2045, 2983 2113  
Email : admin.sales@wiselgroup.indomobil.co.id  
Website : www.johndeere.indomobil.com

Authorized Dealer for John Deere Asia Pte Limited  
Tractor - Farm Equipment